

# PATENT CLAIMS

1. ~~A packaging for a tool with sharp edge, said packaging comprising a suspension device, wherein said packaging comprises a protective and means for supporting the tool in different positions on the sheath, including a first position adapted for sales exposure in which at least a major part of the tool is free of the sheath and exposed for inspection by a prospective buyer, and a second position in which the tool is inserted in the sheath and ready to be handled by a user.~~

2. A packaging according to claim 1, wherein the sheath has a front side and a rear side, and that the tool is supported on the rear side of the sheath by a fastening device, in said first position.

3. A packaging according to claim 2, wherein said sheath comprises an upper sheath part, a lower sheath part and a bottom part, that an opening is provided in the rear side, between the lower sheath part and the bottom part, and into which opening an edge part of the tool may be inserted, for further penetration down into the bottom part, in order for the edge part to be protected by the bottom part in said first position.

4. A packaging according to claim 3, comprising a resiliently deformable part projecting into said opening, at an upper side thereof, which is bent inwards into the lower sheath part when the edge part of the tool is inserted into said opening and further down into the bottom part.

5. Packaging according to claim 3, wherein said bottom part is resiliently connected to the lower sheath part, by means of a resiliently deformable part between the lower sheath part and the bottom part, which allows for the bottom part to be resiliently bent relative to the lower sheath part, thereby making it

10  
15  
20  
25  
30

Sub  
A105

5

10

15

20

25

39

30

12. Packaging according to any of claims 1-8 or 11, wherein the sheath, including all its parts, and the suspension device are made in one piece.